



⚠ This cord may or may not have one or more labels. If labeled, they may be imprinted or on a sticker and may include (but is not limited to) one of the listed model number(s), length, rating or a combination of these.

Packing: Hanked and Tied to Ease Installation

No.	Specification	QTY	Remarks	Mold Embossing List	Tolerances	Approved	Date	StayOnline®					
1	H05VV-F 0.75/3C 300V 70° Black	1 PC		Vendor File # Xuanhua E31387 Xuanhua E257089 Power Fig E257074 Power Fig E50254 StayOnline E250704 StayOnline E50254 Yang Li E152635 Yang Li E341374 SIBMCO E340265 Solihoro E361125 Voxa EG405 Wei Shin E115330 King Card E8854	> 0 ± 0.30 mm >1.0 ± 0.50 mm >10.0 ± 1.0 mm >20.0 ± 2.0 mm Angle: ± 1°	Checked	Date	Customer					
2	Plug BS 1363 UK Black Angled Down	1 PC		StayOnline E50254 Yang Li E152635 Yang Li E341374 SIBMCO E340265 Solihoro E361125 Voxa EG405 Wei Shin E115330 King Card E8854 MSL Enterprises E210037 Guang Zhou Co Ltd E318430 Katus MFD E31793		Drawn	GAC	Date	09APR2026	Model #	P-06bm-uk		
3	Connector IEC 60320 C5 Black	1 PC				Item No.	1689		Material	PVC	Units	mm	
4	LABEL: (40+30) * 30 mm	1 PC	MAX Length = 73mm			Drawing No.	1689		Rev.	B	Scale		