



Mold Markings:
See Mold Embossing List

20A 250V

Jacket Marking:
UL/CSA

Mold Markings:
See Mold Embossing List
20A 250V

This cord may or may not have one or more labels. If labeled, they may be imprinted or on a sticker and may include (but is not limited to) one of the listed model number(s), length, rating or a combination of these.

Packing: Bundled to Ease Installation

No.	Specification	QTY	Remarks	Mold Embossing List	Tolerances	Approved	Date	StayOnline®					
1	SJT 12/3c 105°C Black	1 PC		Vendor File # Xuanhua E31987 Xuanhua E25769 Power Fig E50704 Power Fig E50204 StayOnline E50204 StayOnline E50204 Yung Li E152635 Yung Li E241374 SIBMAC E340266 Scotmore E361125 Vokse E62405 Well-Site E116320 King Cord E85554 MSL Enterprises E210037 Guang Zhou Co Ltd E319420 Kaka MFG E31793	> 0 ± 0.30 mm >1.0 ± 0.50 mm >10.0 ± 1.0 mm >20.0 ± 2.0 mm Angle: ± 1°	Checked	Date	Customer					
2	Plug IEC 60309 Blue	1 PC	Black Base			Drawn	JMB	Date	08MAY2026	Model #	PF320P612C19WS60		
3	Connector IEC 60320 C19 Black	1 PC	WS-Lock			Item No.	81057		Material	PVC	Units	mm	
4	LABEL: (40+30) * 30 mm	1 PC	MAX Length = 73mm			Drawing No.	81057		Rev.	B	Scale		