



⚠ This cord may or may not have one or more labels. If labeled, they may be imprinted or on a sticker and may include (but is not limited to) one of the listed model number(s), length, rating or a combination of these.

Packing: Bundled to Ease Installation

No.	Specification	QTY	Remarks	Mold Embossing List	Tolerances	Approved	Date	StayOnline®					
1	SJT 14/3c 105°C Red	1 PC		Vendor File # Xuanhua E313867 Xuanhua E257089 Power Fig E257054 Power Fig E502004 StayOnline E250704 StayOnline E302004 Yang Li E152626 Yang Li E241374 SBE/MCO E340286 Schniewe E361125 Voxel E62405 Wei Shan E115330 King Choi E26554 MSL Enterprises E210037 Guang Zhou Co Ltd E318430 Katus MFG E31793	> 0m ± 30mm > 0.4m ± 35mm > 1.2m ± 50mm > 3.0m ± 80mm Angle: ± 1°	Checked	Date	Customer					
2	Plug IEC 60320 C14 Red	1 PC				Drawn	GAC	Date	15APR2026	Model #	SPFC1414C1548R		
3	Connector IEC 60320 C15 Red	1 PC	120°C			Item No.	S3982			Material	PVC	Units	mm
4	LABEL: (40+30) * 30 mm	1 PC	MAX Length = 73mm			Drawing No.	S3982		Rev.	C	Scale		